



Technical Data Sheet

Code **GEQL1S350A-DUP-ASE**

Ing. Enea Mattei S.p.A.

PRODUCT SPECIFICATIONS

6/8/18

date

draft

revision

4/12/18

issue

Model **BLADE 4 HXTM-DUP**

Description	WorkShop unit - Duplex		
Arrangement	Silenced		
Series	BLADE STANDARD PRODUCT		
Air End frame	M 75		
Version	n.a.		
OIL cooling medium	Air		
AIR cooling medium	Air		
Modulation	Yes		
Decompression	Yes		
Receiver	ASME		
Inlet nominal pressure	ISO 1217	psi (a)	14.5
Inlet nominal temperature	ISO 1217	°F	68
Relative humidity	ISO 1217	%	0
Motor nominal speed	ISO 1217	rpm	1800
Nominal working pressure		psi (g)	143 (HX)
Maximum working pressure		psi (g)	150
Nominal delivery	(1)	cfm	17.6 (x2)
Terminals absorbed power	(2) (6)	kW	4.3 (x2)
Terminals unload absorbed power		Kw	1.3 (x2)
Noise level (max)	ISO 2151 - @1 mt	dBA	61
Oil carry over		ppm	3
Total heat recovery (up to ...)		%	95
Oil circuit capacity		gallons	1 (x2)

PERFORMANCES (x2)

psi (g)	73		87		100		116		125		150		160		175	
	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW
	-	-	17.92	3.75	17.79	3.92	17.66	4.17	17.60	4.30	-	-	-	-	-	-

ELECTRICAL CHARACTERISTICS (x2)

Electric certification					CEI			
Starting type					Full-Voltage			
Voltage -- Frequency -- Phases					V / Hz / Ph			
Auxiliary circuit tension					V			
Nominal absorbed current	(6)				A			
Minimum supply cables section (33 ft.)					AWG			

MAIN MOTOR (x2)

Nominal power input	kW / HP				4 / 5 (x2)			
Efficiency class					NEMA T			
Efficiency					89.5			
Poles					4			
Protection index					IP 55			
Insulation class					F			

COOLING

Maximum ambient temperature	°F			104
Minimum ambient temperature	°F			34
Outlet AIR temperature	(5) °F			< 95
OIL maximum temperature	°F			248
OIL minimum temperature	°F			176
Fan type				Axial
Cooling AIR flow (minimum)	(3)	cfm		-
Cooling AIR flow (maximum)	(4)	cfm		1001 (x2)
Heat Removal Oil and Aftercooler	(4)	Btu/hr		29352
Fan residual head (minimum)	(3)	Pa		-
Fan residual head (maximum)	(4)	Pa		20
Fan absorbed power (minimum)	(3)	kW		-
Fan absorbed power (maximum)	(4)	kW		0.14
WATER flow	gpm			-
Water INLET temperature	°F			-
Water OUTLET maximum temperature	°F			-
Water minimum suggested pressure	psi (g)			-
Thermal recoverable power	Kcal			-

DRYER

Refrigerant gas				-
Dew point (pressure)	°F			-
Absorbed power	kW			-
Regeneration air percentage	%			-
Supply: Voltage - frequency - phases	V / Hz / Ph			-

DIMENSIONS

AIR outlet connection				Rp 1"
Condensate separator drain connection				-
Condensate drain connection				10 mm (Male) (x2)
Condensate DRYER drain connection				-
Receiver condensate drain connection				Manual (Rp 3/8")
INLET-OUTLET water connections				-
Storage AIR receiver volume	gallons			120
Width	inch			45.0
Length	inch			70.0
Height	inch			60.0
Weight	lbs			1382

NOTES

- (1) - According to ISO 1217 - Annex C (fixed speed) & Annex E (variable speed)
- (2) - Fan included (@ first speed if available) - Dryer input power excluded
- (3) - Fan @ lower speed (OPTIMA @ min speed)
- (4) - Fan @ faster speed (Optima : fan @50Hz)
- (5) - @ reference conditions
- (6) - OPTIMA @ 1500 rpm and 102 psi