



# Technical Data Sheet

Code **GEQL6S350A-ASE**

Ing. Enea Mattei S.p.A.

## PRODUCT SPECIFICATIONS

6/8/18

date

draft

revision

4/12/18

issue

Model **BLADE 7 LXTM-SE**

Description	WorkShop unit		
Arrangement	Silenced		
Series	BLADE <b>STANDARD PRODUCT</b>		
Air End frame	M 75		
Version	n.a.		
OIL cooling medium	Air		
AIR cooling medium	Air		
Modulation	Yes		
Decompression	Yes		
Receiver	ASME		
Inlet nominal pressure	ISO 1217	psi (a)	14.5
Inlet nominal temperature	ISO 1217	°F	68
Relative humidity	ISO 1217	%	0
Motor nominal speed	ISO 1217	rpm	3600
Nominal working pressure		psi (g)	109 (LX)
Maximum working pressure		psi (g)	115
Nominal delivery	(1)	cfm	35.4
Terminals absorbed power	(2) (6)	kW	7.9
Terminals unload absorbed power		Kw	2.07
Noise level (max)	ISO 2151 - @1 mt	dBA	64
Oil carry over		ppm	3
Total heat recovery (up to ...)		%	95
Oil circuit capacity		gallons	1

### PERFORMANCES

psi (g)	73		87		100		115		125		155		160		175	
	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW
	35.9	7.18	35.66	7.54	35.40	7.90	-	-	-	-	-	-	-	-	-	-

### ELECTRICAL CHARACTERISTICS

Electric certification					CEI			
Starting type					Full-Voltage			
Voltage -- Frequency -- Phases					V / Hz / Ph			
Auxiliary circuit tension					V			
Nominal absorbed current	(6)				A			
Minimum supply cables section (33 ft.)					AWG			

### MAIN MOTOR

Nominal power input	kW / HP				7 / 10			
Efficiency class					NEMA T			
Efficiency					%			
Poles					2			
Protection index					IP			
Insulation class					F			

### COOLING

Maximum ambient temperature	°F				104			
Minimum ambient temperature	°F				34			
Outlet AIR temperature	(5)				°F			
OIL maximum temperature					°F			
OIL minimum temperature					°F			
Fan type					Axial			
Cooling AIR flow (minimum)	(3)				cfm			
Cooling AIR flow (maximum)	(4)				cfm			
Heat Removal Oil and Aftercooler	(4)				Btu/hr			
Fan residual head (minimum)	(3)				Pa			
Fan residual head (maximum)	(4)				Pa			
Fan absorbed power (minimum)	(3)				kW			
Fan absorbed power (maximum)	(4)				kW			
WATER flow					gpm			
Water INLET temperature					°F			
Water OUTLET maximum temperature					°F			
Water minimum suggested pressure					psi (g)			
Thermal recoverable power					Kcal			

### DRYER

Refrigerant gas					R134a			
Dew point (pressure)					°F			
Absorbed power					kW			
Regeneration air percentage					%			
Supply: Voltage - frequency - phases					V / Hz / Ph			

### DIMENSIONS

AIR outlet connection					Rp 1/2"			
Condensate separator drain connection					-			
Condensate drain connection					10 mm (Male)			
Condensate DRYER drain connection					(to the atmosphere)			
Receiver condensate drain connection					Manual (Rp 3/8")			
INLET-OUTLET water connections					-			
Storage AIR receiver volume					gallons			
Width					inch			
Length					inch			
Height					inch			
Weight					lbs			

### NOTES

- ( 1 ) - According to ISO 1217 - Annex C (fixed speed) & Annex E (variable speed)
- ( 2 ) - Fan included (@ first speed if available) - Dryer input power excluded
- ( 3 ) - Fan @ lower speed (OPTIMA @ min speed)
- ( 4 ) - Fan @ faster speed (Optima : fan @50Hz)
- ( 5 ) - @ reference conditions
- ( 6 ) - OPTIMA @ 1500 rpm and 102 psi